

21.5 Inch

Closed Frame Android AIO

ATL226



General Touch's breed of Closed Frame Touch computer is characterized by its unified design with AL Alloy frame edges. This sleek and sturdy contraption is loaded with enticing features and options that cater to different requirements including operating on Android, Windows and Linux platforms. The Android version is equipped with a Rockchip processor, while the Windows and Linux versions utilize powerful Intel processors.

Equipped with 10-point responsive PCAP Touch, several I/O interfaces and a high resolution display, connecting and adapting to other devices and peripherals is a breeze for applications in an assortment of scenarios. Also, a Closed frame design has the standard mounting options such as floating or standalone. Hence, GT's Closed frame Touch Computers are well positioned for use in kiosks, POS systems, financial services, self-service applications and information interactive displays.



Gaming



Kiosk



Vending Machine



Industrial Automation

- Support Windows, Linux, Android and mainstream OS
- AL Alloy frame, fashion and sturdy and durable
- General Touch PCAP technology, quality assurance
- VESA Mounting
- 43", 55" large size touch computer with OPS, support 4K solution
- Support customization and OEM/ODM
- Closed frame, compatible with various application

SPECIFICATIONS

Product Name	21.5 Inch Closed Frame Android AIO	
Model	ATL226	
Motherboard Parameters		
SOC	Rockchip® RK3568	
CPU	Quad-core Cortex-A55, up to 2.0GHz	
GPU	Mali-G52	
Memory	2GB, LPDDR4X	
Storage	16GB, eMMC	
OS Support	Android 11	
Wi-Fi & Bluetooth	Onboard Module	
4G LTE	Mini PCI-e Module, optional	
LCD Panel Parameters		
Display Technology	Active Matrix TFT-LCD with LED Backlight	
Aspect Ratio	16:9	
Active Display Area (W x H)	476.64mm x 268.11mm	
Native Resolution	1920 x 1080	
Response Time (Typ.)	18ms	
Display Colors	16.7M	
Luminance (Typ.)	250nits	
Contrast Ratio (Typ.)	3000:1	
Viewing Angle (Typ.)	Horizontal (Left/Right) CR≥10	170° (85°/85°)
	Vertical (Up/Down) CR≥10	170° (85°/85°)
Touchscreen Parameters		
Touch Technology	PCAP	
Touch Point	10	
Light Transmission	≥85%	
Thickness	2.4mm ± 0.3mm	

I/O Port	
LAN	1 x RJ45 (10/100/1000Mbps)
USB	5 x USB 2.0 (Type-A), 1 x USB 3.0 (Type-A)
COM	1 x RS232
Display	1 x HDMI out
4G LTE	1 x Nano SIM slot
Storage Expansion	1 x TF slot
Antenna	1 x SMA-K, available on Wi-Fi & Bluetooth or 4G LTE model
Power	1 x DC Jack (Pin Outer Diameter 2.5mm, optional)
Overall Parameters	
Bezel/Case Colour	Silver/Black
Mounting Options	VESA 100mm x 100mm
Outline Dimensions	529.5mm x 316.5mm x 52.0mm (W x H x D)
Speaker	2 x 2W Built-in, optional
Power Consumption	34W Max
Operating Altitude	≤3000m
Temperature	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non-condensing)	Operating: 20% to 80%, storage: 10% to 90%
Carton Dimensions	TBD
Weight	TBD
MTBF	50,000 Hours Demonstrated
Agency Approvals	CE, FCC
Warranty	2 years

Ordering Information		
Part Name	Part Number	Description
ATL226-RC3-2B00-A02-1.0	10302010042R	2GB LPDDR4X, 16GB eMMC, 2 x 2W Built-in Speakers,Wi-Fi&BT 2 in 1 Module
Optional Accessories		
Part Name	Part Number	Description
US Power Cable	30301010010R	1.5m
EU Power Cable	30301010011R	1.5m
UK Power Cable	30301010018R	1.5m
Power Adapter	30207010005R	Input Voltage Range: 100V - 240V AC Output : 12V DC \pm 5%/4.17A DC Barrel Plug Pin Inner Diameter: 2.5mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>