

15 Inch

Closed Frame Windows AIO

CTL15F



General Touch's breed of Closed Frame Touch computer is characterized by its unified design with AL Alloy frame edges. This sleek and sturdy contraption is loaded with enticing features and options that cater to different requirements including operating on Android, Windows and Linux platforms. The Android version is equipped with a Rockchip processor, while the Windows and Linux versions utilize powerful Intel processors.

Equipped with 10-point responsive PCAP Touch, several I/O interfaces and a high resolution display, connecting and adapting to other devices and peripherals is a breeze for applications in an assortment of scenarios. Also, a Closed frame design has the standard mounting options such as floating or standalone. Hence, GT's Closed frame Touch Computers are well positioned for use in kiosks, POS systems, financial services, self-service applications and information interactive displays.



Gaming



Kiosk



Vending Machine



Industrial Automation

- Support Windows, Linux, Android and mainstream OS
- AL Alloy frame, fashion and sturdy and durable
- General Touch PCAP technology, quality assurance
- VESA Mounting
- 43", 55" large size touch computer with OPS, support 4K solution
- Support customization and OEM/ODM
- Closed frame, compatible with various application

SPECIFICATIONS

| | |
|------------------------|----------------------------------|
| Product Name | 15 Inch Closed Frame Windows AIO |
| Model | CTL15F |
| Motherboard Parameters | |

| | |
|-------------------|---|
| Processor | 5th Generation Intel® Core™ i5 Mobile Dual-Core CPU |
| GPU | Intel® HD Graphics 5500, integrated in CPU |
| Memory | 1 x SO-DIMM Slot, up to 8GB |
| Storage | 1 x mSATA Interface, 2 x SATA Interfaces |
| OS Support | Windows 7/ Windows 8/ Windows 10/ Linux (Note 1) |
| Wi-Fi & Bluetooth | Mini PCI-e Module, optional (Note 2) |
| 4G LTE | Mini PCI-e Module, optional (Note 2) |

LCD Panel Parameters

| | | |
|-----------------------------|--|----------------|
| Display Technology | Active Matrix TFT-LCD with LED Backlight | |
| Aspect Ratio | 4:3 | |
| Active Display Area (W x H) | 304.1mm x 228.1mm | |
| Native Resolution | 1024 x 768 | |
| Response Time (Typ.) | 23ms | |
| Display Colors | 262k | |
| Luminance (Typ.) | 350nits | |
| Contrast Ratio (Typ.) | 2500:1 | |
| Viewing Angle (Typ.) | Horizontal (Left/Right) CR≥10 | 176° (88°/88°) |
| | Vertical (Up/Down) CR≥10 | 176° (88°/88°) |

Touchscreen Parameters

| | |
|--------------------|---------------|
| Touch Technology | PCAP |
| Touch Point | 10 |
| Light Transmission | ≥85% |
| Thickness | 2.4mm ± 0.2mm |

| I/O Port | |
|----------|---|
| LAN | 1 x RJ45 (10/100/1000Mbps) |
| USB | 2 x USB 2.0 (Type-A), 2 x USB 3.0 (Type-A) |
| Display | 1 x VGA out, 1 x HDMI out |
| Audio | 1 x 3.5mm Line out, 1 x 3.5mm Mic in |
| Antenna | 1 x SMA-K, available on Wi-Fi & Bluetooth or 4G LTE model |
| Power | 1 x DC Jack (Pin Outer Diameter 2.5mm, optional) |

| Overall Parameters | |
|---------------------------|--|
| Bezel/Case Colour | Silver/Black |
| Mounting Options | VESA 75mm x 75mm |
| Outline Dimensions | 354.7mm x 278.7mm x 50.8mm (W x H x D) |
| Input Voltage Range | 12V DC \pm 5% |
| Speaker | 2 x 2W Built-in, optional |
| Power Consumption | 72W Max |
| Operating Altitude | \leq 3000m |
| Temperature | Operating: 0°C to 40°C, storage: -20°C to 60°C |
| Humidity (Non-condensing) | Operating: 20% to 80%, storage: 10% to 90% |
| Carton Dimensions | TBD |
| Weight | TBD |
| MTBF | 50,000 Hours Demonstrated |
| Agency Approvals | CE, FCC |
| Warranty | 2 years |

Note 1: The default operating system is Windows 10 IoT Enterprise x64, and Microsoft® Product Key is an optional accessory.

Note 2: There is only 1 Mini PCI-e slot for Wi-Fi & BT 2-in-1 module or 4G LTE module installation.

| Ordering Information | | |
|-------------------------|--------------|--|
| Part Name | Part Number | Description |
| CTL15F-RCP-0B00-A0D-1.0 | 10302020034R | 8GB RAM, 128GB mSATA SSD, 2 x 2W Built-in Speakers |
| Optional Accessories | | |
| Part Name | Part Number | Description |
| Microsoft® Product Key | 30208180003R | Windows 10 IoT Enterprise (OEM) |
| US Power Cable | 30301010010R | 1.5m |
| EU Power Cable | 30301010011R | 1.5m |
| UK Power Cable | 30301010018R | 1.5m |
| Power Adapter | 30207010006R | Input Voltage Range: 100V - 240V AC Output : 12V DC ± 5%/7.5A DC Barrel Plug Pin Inner Diameter: 2.5mm |

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>