

## 21.5 Inch

### Industrial Panel PC

#### CTL225



General Touch's breed of Closed Frame Touch computer is characterized by its unified design with AL Alloy frame. This sleek and sturdy contraption is loaded with enticing features and options that cater to different requirements including operating on Windows and Linux platforms. Those versions utilize powerful Intel 11th Core i5 processors.

Equipped with 10-point responsive PCAP Touch, several I/O interfaces and a high resolution display, connecting and adapting to other devices and peripherals is a breeze for applications in an assortment of scenarios. Also, a Closed frame design has the standard mounting options such as Vesa mounting or standalone. Hence, GT's Closed frame Touch Computers are well positioned for use in kiosks, POS systems, financial services, self-service applications and information interactive displays.

For Industrial scenarios such as production lines, production control or data collection, GT's industrial Panel PCs are reliable companions for smooth and reliable performance that enhances production efficiency.



Kiosk



Vending Machine



Industrial Automation

- Intel 11th Core i5 Processors
- Support Windows, Linux
- AL Alloy frame, fashion and sturdy and durable
- General Touch PCAP technology, quality assurance
- VESA Mounting
- Support customization and OEM/ODM
- Closed frame, compatible with various application
- The diversity of interfaces include USB 3.0, RJ45, RS232, and HDMI

## SPECIFICATIONS

Product Name	21.5 Inch industrial Panel PC
Model	CTL225
Motherboard Parameters	

Processor	11th Generation Intel® Core™ i5 Mobile Quad-Core CPU
GPU	Intel® Iris® Xe Graphics eligible, integrated in CPU
Memory	1 x DDR4 SO-DIMM Slot, up to 64GB
Storage	1 x SATA3.0 Interface, 1 x mSATA Interface, 1 x M.2 Interfaces
OS Support	Windows 10/Windows11/Linux (Note 1)
Wi-Fi & Bluetooth	Mini PCI-e Module, optional
4G LTE	Mini PCI-e Module, optional

### LCD Panel Parameters

Display Technology	Active Matrix TFT-LCD with LED Backlight	
Aspect Ratio	16:9	
Active Display Area (W x H)	476.64mm x 268.11mm	
Native Resolution	1920 x 1080	
Response Time (Typ.)	18ms	
Display Colors	16.7M	
Luminance (Typ.)	250nits	
Contrast Ratio (Typ.)	3000:1	
Viewing Angle (Typ.)	Horizontal (Left/Right) CR≥10	178° (89°/89°)
	Vertical (Up/Down) CR≥10	178° (89°/89°)

### Touchscreen Parameters

Touch Technology	PCAP
Touch Point	10
Light Transmission	≥85%
Thickness	2.4mm ± 0.2mm

I/O Port	
LAN	2 x RJ45 (10/100/1000Mbps)
USB	4 x USB 3.0 (Type-A)
COM	1 x RS232
Display	2 x HDMI out
Audio	1 x 3.5mm Phone Jack, Line out/Mic 2 in 1
Antenna	1 x SMA-K, available on Wi-Fi & Bluetooth or 4G LTE model
Power	1 x DC Jack (Pin Outer Diameter 2.5mm)

Overall Parameters	
Bezel/Case Colour	Black
Mounting Options	VESA 100mm x 100mm
Outline Dimensions	510.4mm x 307.0mm x 50.3mm (W × H × D)
Input Voltage Range	12V DC ± 5%
Speaker	2 x 2W Built-in, optional
Power Consumption	89W Max
Operating Altitude	≤3000m
Temperature	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non-condensing)	Operating: 20% to 80%, storage: 10% to 90%
Carton Dimensions	TBD
Weight	TBD
MTBF	50,000 Hours Demonstrated
Agency Approvals	CE, FCC
Warranty	2 years

Note 1: The default operating system is Windows 10 IoT Enterprise x64, and Microsoft® Product Key is an optional accessory.

Ordering Information		
Part Name	Part Number	Description
CTL225-RCM-2B00-A0D-1.0	10302020103R	8GB RAM, 128GB mSATA SSD, 2 x 2W Built-in Speakers, WiFi&BT 2 in1 Module
Optional Accessories		
Part Name	Part Number	Description
Microsoft® Product Key	30208180003R	Windows 10 IoT Enterprise (OEM)
US Power Cable	30301010010R	1.5m
EU Power Cable	30301010011R	1.5m
UK Power Cable	30301010018R	1.5m
Power Adapter	30207010006R	Input Voltage Range: 100V - 240V AC Output : 12V DC ± 5%/7.5A DC Barrel Plug Pin Inner Diameter: 2.5mm

Go to [www.generaltouch.com](http://www.generaltouch.com) for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

**Tel:** 0086-28-85124120

**Fax:** 0086-28-85124115

**E-mail:** [info@generaltouch.com](mailto:info@generaltouch.com)

<http://www.generaltouch.com>