

21.5 Inch

Closed Frame Windows AIO



General Touch's breed of Closed Frame Touch computer is characterized by its unified design with AL Alloy frame edges. This sleek and sturdy contraption is loaded with enticing features and options that cater to different requirements including operating on Android, Windows and Linux platforms. The Android version is equipped with a Rockchip processor, while the Windows and Linux versions utilize powerful Intel processors.

Equipped with 10-point responsive PCAP Touch, several I/O interfaces and a high resolution display, connecting and adapting to other devices and peripherals is a breeze for applications in an assortment of scenarios. Also, a Closed frame design has the standard mounting options such as floating or standalone. Hence, GT's Closed frame Touch Computers are well positioned for use in kiosks, POS systems, financial services, self-service applications and information interactive displays.



Gaming



Kiosk



Vending Machine



Industrial Automation

- Support Windows, Linux, Android and mainstream OS
- AL Alloy frame, fashion and sturdy and durable
- General Touch PCAP technology, quality assurance
- VESA Mounting
- Support customization and OEM/ODM
- Closed frame, compatible with various application

SPECIFICATIONS

Product Name	21.5 Inch Closed Frame Windows AIO
Model	CTL226
Motherboard Parameters	

Processor	12th Generation Intel® Core™ i3 / i5 Processors
GPU	Integrated in CPU (Note 1)
Memory	2* DDR4 SO-DIMM Slot, up to 64GB
Storage	1 x SATA3.0 Interface, 1 x M.2 Slot
OS Support	Windows 10/ Linux (Note 2)
Wi-Fi & Bluetooth	M.2 Module, optional
4G/5G LTE	M.2 Module, optional

LCD Panel Parameters

Display Technology	Active Matrix TFT-LCD with LED Backlight	
Aspect Ratio	16:9	
Active Display Area (W x H)	476.6mm x 268.1mm	
Native Resolution	1920 x 1080	
Response Time (Typ.)	18ms	
Display Colors	16.7M	
Luminance (Typ.)	250nits	
Contrast Ratio (Typ.)	3000:1	
Viewing Angle (Typ.)	Horizontal (Left/Right) CR≥10	178° (89°/89°)
	Vertical (Up/Down) CR≥10	178° (89°/89°)

Touchscreen Parameters

Touch Technology	PCAP
Touch Point	10
Light Transmission	≥85%
Thickness	2.4mm ± 0.3mm

I/O Port	
LAN	1 x RJ45 (10/100/1000Mbps)
USB	2 x USB 2.0 (Type-A), 2 x USB 3.0 (Type-A)
Display	1 x VGA out, 1 x HDMI out
Audio	1 x 3.5mm Line out, 1 x 3.5mm Mic in
Antenna	1 x SMA-K, available on Wi-Fi & Bluetooth or 4G/5G LTE module
Power	1 x DC Jack (Pin Outer Diameter 2.5mm, optional)

Overall Parameters	
Bezel/Case Colour	Silver/Black
Mounting Options	VESA 75mm x 75mm
Outline Dimensions	529.5mm x 316.5mm x 49.3mm (W x H x D)
Input Voltage Range	12V DC \pm 5%
Speaker	2 x 2W Built-in, optional
Power Consumption	90W Max
Operating Altitude	\leq 3000m
Temperature	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non-condensing)	Operating: 20% to 80%, storage: 10% to 90%
Carton Dimensions	TBD
Weight	TBD
MTBF	50,000 Hours Demonstrated
Agency Approvals	CE, FCC
Warranty	2 years

Note 1: For 12th Gen i3 cpu, it's the Intel® UHD Graphics for 12th Gen Intel® Processors; for 12th Gen i5 cpu, it's the Intel® Iris® Xe Graphics eligible.

Note 2: The default operating system is Windows 10 IoT Enterprise x64, and Microsoft® Product Key is an optional accessory.

Ordering Information		
Part Name	Part Number	Description
CTL226-RCE-2B00-A0D-1.0	10302020146R	Intel 12th Gen i3, 8GB RAM, 128GB SSD, 2 x 2W Built-in Speakers, Wi-Fi&BT 2 in 1 Module
CTL226-RCF-2B00-A0D-1.0	10302020139R	Intel 12th Gen i5, 8GB RAM, 128GB SSD, 2 x 2W Built-in Speakers, Wi-Fi&BT 2 in 1 Module
Optional Accessories		
Part Name	Part Number	Description
Microsoft® Product Key	30208180003R	Windows 10 IoT Enterprise (OEM)
US Power Cable	30301010010R	1.5m
EU Power Cable	30301010011R	1.5m
UK Power Cable	30301010018R	1.5m
AU Power Cable	30301010015R	1.5m
Power Adapter	30207010006R	Input Voltage Range: 100V - 240V AC Output : 12V DC \pm 5%/7.5A DC Barrel Plug Pin Inner Diameter: 2.5mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>