

27 Inch

## LED-Framed Monitor



The LED-Framed monitor dazzles with ambient lighting effects on the front and/or back of its sides. The color, style, and rhythm of the lights can be used as adornments, alerts, attractions, flags, indicators or fanfare that will surely boost the interactive functions of a display for both the users and operators.

To match different design styles, General Touch offers various LED light strip designs, including Front design with LED lights visible from the front, Edge design and Halo design with LED lights visible from the front and sides. The rear of the LED-Framed monitor has multiple design options too, such as rear-fire LED strips on four sides, U-shaped strips on three sides, or two parallel strips on the short or long edges. These combinations offer a wide variety of style and luster.

The GT LED-Framed monitor stands out with their exceptional lighting effects, featuring no hot spots, dark spots, and dark corners, and ensuring a high level of uniformity with finely crafted, well-sealed, and free from LED light leakage. To facilitate customer control over the LEDs, GT provides protocols and controllers for customers to choose from. The LED controllers can be embedded or external, and it also supports customer-supplied controllers. The lighting effects offer dozens of standard modes and can be customized to meet specific customer requirements.

LED-Framed monitors have been widely used in various scenes and domains, including gaming, kiosks, entertainment, EV chargers, meetings, and way-finding. The landscape, portrait, and VESA mounting options allow for quick and convenient integration with different environments, fulfilling customers' demands for high-quality dual interaction experiences.



Gaming



Kiosk



Vending Machine

- LED-Framed, Edge design
- No hot spot, no dark spot, no dark corner, high level uniformity
- Optical bonding technology, providing a more authentic display
- Metal frame, precisely and finely crafted
- Extremely narrow border
- Well sealed, non LED light leakage
- True flat, closed frame, compatible with various application

## SPECIFICATIONS

Product Name	27 Inch LED-Framed Monitor	
Model	ONL277	
LCD Panel Parameters		
Display Technology	Active Matrix TFT-LCD with LED Backlight	
Aspect Ratio	16:9	
Active Area (W x H)	597.89mm × 336.31mm	
Native Resolution	1920 × 1080 @ 60Hz	
Response Time (Typ.)	14ms	
Display Colors	16.7M	
Luminance (Typ.)	400nits	
Contrast Ratio (Typ.)	1000:1	
Viewing Angle (Typ.)	Horizontal: CR≥10 89°/89°    Vertical: CR≥10 89°/89°	
Screen Parameters		
Cover Glass Treatment	Strengthened	
Cover Glass Surface Treatment	Optional: Anti-glare	
Impact Resistance Level	IK07	
Thickness (Total)	3.0mm	
Light Transmission	≥ 90%	
Overall Parameters		
Case/Bezel Color	Black	
Mounting Options	VESA: 100mm × 100mm, 75mm × 75mm	
Outline Dimensions (W×H×D)	628.0mm × 360.3mm × 57.8mm	
Power Supply	Input Voltage Range: Monitor: +12VDC ± 5%, Coaxial power jack 2.5mm pin outer diameter Optional LED controller (External): +12VDC ± 5%, Coaxial power jack 2.5mm pin outer diameter	
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu	
Power Consumption (Max.)	36W (Monitor with RGB LED Lights)	
Operating Altitude	≤ 3000m	
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C	
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%	
I/O	VGA, DVI, DP	
Accessories	Optional	
Carton Box Dimensions	740mm (L) × 275mm (W) × 492mm (H), 2 units in one carton	
Weight	Net: 9kg, Gross: 25kg	
MTBF	50,000 hours demonstrated	

LED Lights Color	Multicolor
LED Lights Location	2 LED lights bar (Front, Edge, see drawing for details)
LED Controller (External)	Optional
Agency Approvals	CE, FCC, UKCA
Warranty	3 years

Ordering Information		
Model	Part Number	Description
ONL277-R03000-0P2F20-1.0	10202010422R	27", 16:9, FHD, 400nits, non-touch, USB, VGA/DVI/DP, 2 LED lights bar (front, edge)

Optional Accessories		
Model	Part Number	Description
VGA Cable	30302040001R	VGA Cable 1500mm
DVI Cable	30302020002R	DVI Cable Male-Male 18+1 1500mm
DP Cable	30302010001R	DP Cable Male-Male 1500mm
LED Controller Kit	20701040010R	12 V / 50 W Addressable LED Controller Kit
<p><b>Note:</b> Includes a 1000mm LED strip cable.            If you want to design the LED strip cable according to your application, please adopt the unshielded and non-twisted wires. The length should be no more than 2m, and the wire diameter should be more than 20AWG.            Please feel free to contact us if you need assistance.</p>		
Adapter	30207010005R	Power Adapter 12V / 50W / 2.5mm / 1500mm
Power Cable	30301010018R	UK
	30301010011R	EU
	30301010010R	US

Go to [www.generaltouch.com](http://www.generaltouch.com) for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: [info@generaltouch.com](mailto:info@generaltouch.com)