

13.3 Inch

Open Frame Touchmonitor



For touchmonitors which will be housed in cabinets, the premier choice is the open frame PCAP series. Over the last twenty years, General Touch's open framed touchmonitors have gone through progressive transformation in order to keep up with advancing technology and market expectations. The open frame PCAP touchmonitor series primarily offers true-flat screen and PCAP touch to guarantee the satisfaction of users, and cover glass is easily customizable, so this design comes with mounting options that could be adjusted to fit the varying thickness in today's cabinets.

As industrial components are used, this series is taking the 'High Road', namely High Resolution, High Brightness, High Performance, High Reliability. In short, it is a High Grade touchmonitor that could withstand long time continual operation. With a 3-year warranty and sizes ranging 10.1-43 inches, General Touch's PCAP Open Framed touchmonitors have been widely adopted in retail, gaming, self-service, finance, transportation, conference, education and other industries.



Gaming



Kiosk



Vending Machine



Industrial Automation

- Open frame, with Industry quality and long lifespan
- General Touch PCAP technology, quality assurance
- Range size from 10.1 inch to 43 inch, one stop for you
- 3 years warranty
- Edge-to-edge after assembly, maintenance free
- Industrial-grade raw materials, better for industry

SPECIFICATIONS

Name	13.3 Inch Open Frame Touchmonitor
Model	OTL133
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	293.76mm × 165.24mm
Native Resolution	1920×1080@60Hz
Response Time (Typ.)	30ms
Display Colors	262K
Luminance (Typ.)	600nits, with PCAP 500nits
Contrast Ratio (Typ.)	800:1
Viewing Angle (Typ.)	Horizontal (Left/Right) CR≥10 85°/85° Vertical (Up/Down) CR≥10 85°/85°
Touch Screen Parameters	
Touch Technology	PCAP
Cover Glass Treatment	Strengthened
Cover Glass Surface Treatment	Optional: Anti-Glare
Impact Resistance Level	IK08
Active Area(W x H)	294.8mm × 166.2mm ± 0.3mm
Thickness(Total)	5.3mm ± 0.3mm
Light Transmission	≥83%
Response Time	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Gray
Mounting Options	VESA: 75mm × 75mm, Side mount
Outline Dimensions (W×H×D)	328.0mm × 213.0mm × 41.5mm
Power Supply	Input Voltage Range: +12VDC ± 5%, Coaxial power jack 2.5mm pin outer diameter
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 12W
Speaker	Optional

Operating Altitude	≤3000m
Temperature Range	Operating: 0°C to 40°C, Storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, Storage: 10% to 90%
I/O	VGA, HDMI, USB (Type B, For Touch)
Accessories	Cables: VGA×1, USB×1, 1.5m Length
Carton Box Dimensions	480mm (L) × 387mm (W) × 390mm (H), 4 units in one carton
Weight	Net: 3.46kg, Gross: 17kg
MTBF	50,000 hours demonstrated
Agency Approvals	CE, FCC, CCC, UKCA
Warranty	3 years

Ordering Information

Model	Part Number	Description
OTL133-RC6000-UH6200-2.0	10202010663R	13.3", 16:9, 600nits, PCAP, USB, VGA & HDMI, Gray

Contact sales for other options

Optional Accessories

Model	Part Number	Description
Adapter	30207010005R	12V/4.17A, DC Cable: 1500mm, DC barrel plug 2.5mm pin inner diameter
	30301010018R	UK
Power Cable	30301010011R	EU 1500mm
	30301010010R	US
HDMI Cable	30302030001R	1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>