

## 43 Inch

## **Open Frame Touchmonitor**



For touchmonitors which will be housed in cabinets, the premier choice is the open frame PCAP series. Over the last twenty years, General Touch's open framed touchmonitors have gone through progressive transformation in order to keep up with advancing technology and market expectations. The open frame PCAP touchmonitor series primarily offers true-flat screen and PCAP touch to guarantee the satisfaction of users, and cover glass is esaily to customize, so this design comes with mounting options that could be adjusted to fit the varying thickness in today's cabinets.

As industrial components are used, this series is taking the 'High Road', namely High Resolution, High Brightness, High Performance, High Reliability. In short, it is a High Grade touchmonitor that could withstand long time continual operation. With a 3-year warranty and sizes ranging 10.1-43 inches, General Touch's PCAP Open Framed touchmonitors have been widely adopted in retail, gaming, self-service, finance, transportation, conference, education and other industries.



Gaming



Kiosk



Vending Machine



Industrial Automation

- Open frame, with Industry quality and long lifespan
- Range size from 10.1 inch to 43 inch, one stop for you
- Industryial-grade raw materials, better for industry
- · General Touch PCAP technology, quality assurance
- 3 years warranty
- · Edge-to-edge after assembly, maintenance free



## **SPECIFICATIONS**

SPECIFICATIONS	
Name	43 Inch Open Frame Touchmonitor
Model	OTL436
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	940.9mm × 529.25mm
Native Resolution	1920×1080@60Hz
Response Time (Typ.)	8ms
Display Colors	16.7M
Luminance (Typ.)	400nits, with PCAP 332nits
Contrast Ratio (Typ.)	1200:1
Viewing Angle (Typ.)	Horizontal (Left/Right) CR≥10 89°/89°  Vertical (Up/Down) CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	PCAP
Cover Glass Treatment	Strengthened
Cover Glass Surface Treatment	Optional: Anti-Glare
Impact Resistance Level	IK07
Active Area(W x H)	941.18mm × 529.42mm±0.5mm
Thickness(Total)	4.8mm±0.3mm
Light Transmission	≥83%
Response Time	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Gray back cover
Mounting Options	VESA: 400mm ×200mm, Side Mounting
Outline Dimensions $(W \times H \times D)$	1021.0mm × 608.7mm × 54.2mm
Power Supply	Input Voltage Range: 100~240V AC, 50~60Hz

Control (Back): Power, Auto, Up, Down, Menu

MAX: 80W

Speaker Optional

On Screen Display (OSD)

Power Consumption



Operating Altitude	≤3000m
Temperature Range	Operating: 0°C to 40°C, Storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, Storage: 10% to 90%
I/O	VGA, DVI, HDMI, DP, USB (Type B, For Touch)
Accessories	Cables: VGA×1, USB×1, 1.5m Length
Carton Box Dimensions	1190mm (L) × 240mm (W) × 780mm (H)
Weight	Net: 24.2kg, Gross: 31.6kg
MTBF	50,000 hours demonstrated
Agency Approvals	CE, FCC, UKCA
Warranty	3 years

Ordering Information		
Model	Part Number	Description
OTL436-RPCZ05-UHPCDAGN4	10202010115R	43", 16:9, 400nits, PCAP, USB, VGA & HDMI, Gray

Contact sales for other options

Optional Accessories			
Model	Part Number	Description	
	30301010018R	UK	
Power Cable	30301010011R	EU	1500mm
	30301010010R	US	
HDMI Cable	30302030001R		1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120
Fax: 0086-28-85124115
E-mail: info@generaltouch.com
http://www.generaltouch.com