

43 Inch

LED-Framed Touchmonitor

OTL437




The LED-Framed touchmonitor dazzles with ambient lighting effects on the front and/or back of its sides. The color, style, and rhythm of the lights can be used as adornments, alerts, attractions, flags, indicators or fanfare that will surely boost the interactive functions of a touch display for both the users and operators.

To match different design styles, General Touch offers various LED light strip designs, including Front design with LED lights visible from the front, Edge design and Halo design with LED lights visible from the front and sides. The rear of the LED-Framed monitor has multiple design options too, such as rear-fire LED strips on four sides, U-shaped strips on three sides, or two parallel strips on the short or long edges. These combinations offer a wide variety of style and luster.

The GT LED-Framed touchmonitor stands out with their exceptional lighting effects, featuring no hot spots, dark spots, and dark corners, and ensuring a high level of uniformity with finely crafted, well-sealed, and free from LED light leakage. To facilitate customer control over the LEDs, GT provides protocols and controllers for customers to choose from. The LED controllers can be embedded or external, and it also supports customer-supplied controllers. The lighting effects offer dozens of standard modes and can be customized to meet specific customer requirements.

LED-Framed touchmonitors have been widely used in various scenes and domains, including gaming, kiosks, entertainment, EV chargers, meetings, and way-finding. The landscape, portrait, and VESA mounting options allow for quick and convenient integration with different environments, fulfilling customers' demands for high-quality dual interaction experiences.



- LED-Framed, Edge design, no hot spot, dark spot, dark corner, high level uniformity
- Narrow black border, 4 sides 15.5mm
- 4K resolution
- Metal frame, precisely and finely crafted
- Well sealed, non LED light leakage
- True flat, closed frame, compatible with various application

SPECIFICATIONS

Product Name	43 Inch LED-Framed Touchmonitor	
Model	OTL437	
LCD Panel Parameters		
Display Technology	Active Matrix TFT-LCD with LED Backlight	
Aspect Ratio	16:9	
Active Area (W x H)	941.18mm × 529.42mm	
Native Resolution	3840 × 2160 @ 60Hz	
Response Time (Typ.)	8ms	
Display Colors	1.07B	
Luminance (Typ.)	500nits	
Contrast Ratio (Typ.)	1200:1	
Viewing Angle (Typ.)	Horizontal: CR≥10 89°/89° Vertical: CR≥10 89°/89°	
Touch Screen Parameters		
Touch Technology	PCAP	
Surface Treatment	Tempered	
Thickness (Total)	5.3mm	
Light Transmission	≥ 83%	
Response Time (Typ.)	10ms	
Touch Screen Interface	USB	
Touch Point	10	
Overall Parameters		
Case/Bezel Color	Black	
Mounting Options	VESA: 400mm × 400mm	
Outline Dimensions (W×H×D)	575.5mm × 987.2mm × 64.2mm	
Power Supply	Input Voltage Range: Monitor: +24 VDC ± 5%, 4 PIN plug or 6 PIN mating Molex 3901-2060 RGB LED Lights: +12VDC ± 5%, mating Molex 43025-0600 Optional LED controller (External): +12VDC ± 5%, Coaxial power jack 2.5mm pin outer diameter	
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu	
Power Consumption (Max.)	100W (Monitor without RGB LED Lights) 30W (RGB LED Lights)	
Operating Altitude	≤ 3000m	
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C	
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%	
I/O	HDMI, HDMI, DP, USB (Type B)	
Accessories	Cables: USB × 1, 1.5m Length	

Carton Box Dimensions	1110mm (L) × 240mm (W) × 755mm (H), 1 unit in one carton
Weight	Net: TBD kg, Gross: TBD kg
MTBF	50,000 hours demonstrated
LED Lights Color	Multicolor
LED Lights Location	4 LED lights bar (Front & Edge)
LED Controller (External)	Optional
Agency Approvals	CE, FCC, UL
Warranty	3 years

Ordering Information		
Model	Part Number	Description
OTL437-LC6000-UD5U40-1.0	10202010657L	43", UHD, 16:9, 500nits, PCAP, USB, HDMI/HDMI/DP, 4 LED lights bar (Front & Edge)

Optional Accessories		
Model	Part Number	Description
HDMI Cable	30302030001R	HDMI Cable Male-Male 1500 mm
DP Cable	30302010001R	DP Cable Male-Male 1500 mm
LED Controller Kit	20701040010R	12 V / 50 W Addressable LED Controller Kit
Adaptor	30207010024R	Power Adapter 24 V / 150 W / 4 Pin / 1200 mm
Power Cable	30301010018R	UK
	30301010011R	EU 1500mm
	30301010010R	US

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com