

23.6 Inch

Circular Touchmonitor



The 23.6" circular monitor is a true eye-catcher designed to grab attention in any environment with its unique round form factor - perfect for digital signage applications, gaming machines, or anywhere you want to showcase content in an engaging and memorable way.

Utilizing GT's PCAP multi-touch technology, it provides a responsive touch experience for interacting with content using intuitive gestures. Built with an industrial-grade LCD panel offering a crisp full HD resolution of 1280x1280, vibrant colors and clear imagery are optimized for extended commercial/industrial operation. Setting up this innovative circular multi-touch display is hassle-free with true plug-and-play capability requiring no special touch drivers, saving valuable time and effort during installation and integration.



Gaming



Kiosk



Vending
Machine

- Circular, eye-catching
- PCAP powered by General Touch, quality assurance, plug and play
- High resolution 1280 × 1280
- True flat, Closed Frame, compatible with various application

SPECIFICATIONS

Product Name	23.6 Inch Circular Touchmonitor	
Model	OTR245	
LCD Panel Parameters		
Display Technology	Active Matrix TFT-LCD with LED Backlight	
Aspect Ratio	1:1	
Active Area (W x H)	599.42mm × 599.42mm	
Native Resolution	1280 × 1280 @ 60Hz	
Response Time (Typ.)	14ms	
Display Colors	16.7M	
Luminance (Typ.)	1500nits	
Contrast Ratio (Typ.)	1000:1	
Viewing Angle (Typ.)	Horizontal: CR≥10 89°/89° Vertical: CR≥10 89°/89°	
Touch Screen Parameters		
Touch Technology	PCAP	
Cover Glass Treatment	Strengthened	
Cover Glass Surface Treatment	Optional: Anti-glare	
Impact Resistance Level	IK07	
Thickness (Total)	3.5mm	
Light Transmission	≥ 83%	
Response Time (Typ.)	10ms	
Touch Screen Interface	USB	
Touch Point	10	
Overall Parameters		
Case/Bezel Color	Black	
Mounting Options	VESA: 200mm × 150mm	
Outline Dimensions (W×H×D)	674.6mm × 674.6mm × 55.6mm	
Power Supply	Input Voltage Range: +24 VDC ± 5%, 4 PIN plug or 6 PIN mating Molex 3901-2060	
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu	
Power Consumption (Max.)	100W	
Operating Altitude	≤ 3000m	
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C	
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%	

I/O	HDMI, DP, USB (Type B)
Accessories	Optional
Carton Box Dimensions	785mm (L) × 785mm (W) × 185mm (H), 1 unit in one carton
Weight	Net: 11.9 kg, Gross: 17.6 kg
MTBF	50,000 hours demonstrated
Agency Approvals	CE, FCC, UKCA
Warranty	3 years

Ordering Information		
Model	Part Number	Description
OTR245-RC4000-UDBT00-1.0	10202010567R	23.6", circular, 1:1, 1500nits, PCAP, USB, HDMI & DP

Optional Accessories		
Model	Part Number	Description
USB Cable	30302050006R	USB Cable A Male-B Male 1500mm
HDMI Cable	30302030001R	HDMI Cable A Male-A Male 1500mm
DP Cable	30302010001R	DP Cable Male-Male 1500mm
Adapter	30207010024R	Power Adapter 24V/150W /4Pin/1200mm
Power Cable	30301010018R	UK
	30301010011R	EU
	30301010010R	US

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>