

## 27" Open Frame

# DuraBrite Series Outdoor High Bright Monitors



Operating outdoor kiosks is not for the fainthearted. The average touch display just won't do because of the numerous 'moving parts' in an outdoor environment. You would need both brains and brawn for successful deployment. To take on these physical challenges, General Touch has come up with the DuraBrite series outdoor high bright monitors. Currently available in sizes from 7 to 32 inches, the state-of-the-art DuraBrite series have been carefully designed and produced with innovative enhancements and capabilities. These enhancements would facilitate optimal performance in adverse environmental conditions, making the series ideal for use in payment terminals, self-service kiosks, EV charging stations, ticketing machines, vending machines, outdoor signage and more.



EV Charging Station



Self-service Kiosk



Vending Machine



Ticketing Machines



Parking Pay Station



Outdoor Signage

### Features & Benefits

- High-Tni up to 105° allows a wide operating temperature range from -20°C to 60°C, eradicating any fear of display black-out.
- Brightness up to 1500 nits and anti-glare coating delivers better visuals and readability even in direct sunlight.
- 50K hours LED lifetime - 50,000 hours of MTBF for lasting 24/7 operation.
- UV&IR protection minimizes internal heat accumulation and decelerates components aging significantly.
- UV-resistant ink prevents the screen printing from peeling effectively.
- The touch performance is heightened to facilitate smooth operations even when there are water droplets on the touch glass.
- Advanced optical bonding takes interior fogging out of the equation.
- The iThermal system achieves dynamic heat dissipation and optimal cooling effect through intelligent thermal management.
- Automatic brightness adjustment corresponds with ambient light to ensure 24/7 stable performance and to extend LCD panel lifespan.
- The metal parts have been beefed up with rustproofing for all-year outdoor deployment.
- When the touchmonitor is properly fitted to the kiosk without any gaps, the waterproof and dustproof rating can reach IP65 & Nema 4x , further fortifying the whole touch unit.

## SPECIFICATIONS

Name	27 Inch Outdoor High Bright Monitor
Model	RSL276-RC80A0-UDB2L0-1.0
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	597.89 × 336.31mm
Native Resolution	1920 × 1080 @ 60Hz
Response Time (Typ.)	14ms
Display Colors	16.7million
Luminance (Typ.)	1500nits, with P-Cap 1050nits(touch monitor), High TNI: 105°C
Contrast Ratio (Typ.)	1000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89° /89°
	Vertical (up/down) CR≥10 89° /89°
Touch Screen Parameters	
Touch Technology	PCAP
Cover Glass Treatment	Strengthened
Cover Glass Surface Treatment	Anti-Glare
Impact resistance Level	IK10
View Area(W x H)	596.9 × 335.3 ± 0.3mm
Thickness(Total)	7.5 ± 0.3mm
Light Transmission	≥70%
Response Time	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Gray
Mounting Options	VESA: 100 × 100 mm, 100 × 200 mm, Side mounting
Outline Dimensions	658.0mm × 414.9mm × 72.4mm
Power Supply	24V DC
On Screen Display (OSD)	Power, Auto, Up, Down, Menu
Power Consumption	MAX: 110W
Speaker	NA

Light sensor	Yes
Operating Altitude	≤3000m
Temperature Range & Humidity (Non Condensing)	Operating: -20°C to +60°C, Humidity: 20% to 80%; Storage: -20°C to +70°C, Humidity: 10% to 90%;
I/O	VGA, DVI, HDMI, DP, USB (Type B, for touch)
Accessories	Cables: VGA × 1, USB × 1, 1.5m Length
Carton Box Dimensions	656mm (L) × 222mm (W) × 454mm (H)
Weight	Net: 14.71kg Gross: 19.8kg
MTBF	50,000 hours demonstrated
Agency Approvals	CE FCC UKCA
Warranty	1 year

Ordering Information		
Model	Part Number	Description
RSL276-RC80A0-UDB2L0-1.0	10202010698R	27", Open frame, 16:9, 1500nits, PCAP, USB, VGA & DVI HDMI & DP, Sunlight readable, Outdoor, Gray
<i>Contact sales for other options</i>		

Optional Accessories			
Model	Part Number	Description	
Adapter	30207010024R	24V/6.25A, DC Cable: 1200mm	
Power Cable	30301010018R	UK	1500mm
	30301010011R	EU	
	30301010010R	US	
HDMI Cable	30302030001R	1500mm	
DP Cable	30302010001R	1500mm	

Go to [www.generaltouch.com](http://www.generaltouch.com) for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: [info@generaltouch.com](mailto:info@generaltouch.com)

<http://www.generaltouch.com>